

REFRIGERATION

PRODUCTS and

REFRESHMENT

CENTERS



Refrigeration Products | Outdoor Rated Refrigerator & Kegerator

Outdoor Rated Refrigerator

3589-DR (Model w/ right door hinge, shown) **3589-DL** (Model w/ left door hinge)

- Cut-out Dimensions: 24"w x 27"d x 35"h

- 5.1 cubic feet of storage
- Internal digital thermometer
- Adjustable shelves
- LED internal light
- Lock and key
- Fire Magic[®] style handle
- Extra storage space available in the door
- UL listed for outdoor use



Outdoor Rated Kegerator

3594-DR (Model w/right door hinge) **3594-DL** (Model w/left door hinge, shown)

- Cut-out Dimensions: 24"w x 27"d x 35"h
- Double tap kegerator
- · Internal digital thermometer
- Closed door assist with lock and key system ensures your beverages will stay cold and secure
- Can accommodate a full, half, quarter or one-sixth sized kegs
- Metal shelves included to convert to a full refrigerator when not storing a keg
- UL listed for outdoor use



REFRIGERATIONPRODUCTS



Lock and Key

Lock and key to ensure beverages will stay cold and secure.



Digital Thermometer

Internal digital thermometer to maintain proper temperature for your beverages.



Kegerator accommodates a full, half, quarter or one-sixth sized kegs.

REFRIGERATION **PRODUCTS**



AUTOMATIC OUTDOOR ICE MAKER



Stores up to 27 lbs of ice



Produces clear, bell-shaped ice cubes

Refrigeration Products | Refrigerators & Ice Maker



Refrigerator

3598

- Cut-out Dimensions: 20"w x 21%"d x 34%"h
- Interior light and security lock and key.
- Reversible door hinge.
- When used outdoors, it must be installed in an enclosure.

Automatic Outdoor Ice Maker

5597

- Minimum Cut-out Dimensions: 15¼"w x 25¼"d x 34"h
- Outdoor rated ice maker produces 63 lbs of ice in a 24 hour period.
- Capable of storing up to 27 lbs of individual clear, bell-shaped ice cubes.
- UL listed for outdoor use.
- Continuously produces ice on demand as ice used.
- Suitable for outdoor or indoor applications.
- Reversible door features horizontal handle that doubles as a Towel Bar.

SPECIFICATIONS
15" w x 25¼" d x 34"- 35" h*
120V / 9A Max / 60Hz
Max 500W
110 lbs
140 lbs
63 lbs per 24 hours**
up to 27 lbs

^{*} Height may be adjusted from 34" to 35". Depth includes door and handle.



Premium Refrigerator

3598-DR (Model w/right door hinge, shown) **3598-DL** (Model w/left door hinge)

- Cut-out Dimensions: 20"w x 21%"d x 34%"h
- 4.0 cubic feet of storage space.
- Custom-designed door is fabricated with a heavy-duty handle and square edges to match doors, drawers, and other accessories.
- Handy lock keeps contents safe.
- · When used outdoors, it must be installed in an enclosure.





Horizontal handle that doubles as a towel bar (towel included)



Ice Scoop Included

^{**} Actual quantity of ice produced can vary with conditions.

Refreshment Centers | Refreshment Centers, Beverage Butler, & Bar Caddy



Refreshment Center

3596A

- Cut-out dimensions: 25"w x 25"d x 12"h
- Insulated walls, bottom drain, in-front shelving, attached bottle opener, included drain kit, Echelon styled face and hinged removable lid.



Drop-In Refreshment Center

33596

- Cut-out dimensions: 25"w x 23%"d x 12%"h
- Use like an ice cooler in your grill island to keep soda, beer or other beverages cold and frosty. Includes handy drain kit and hinged removable insulated lid.



Beverage Butler

3835

1D-S0

- Cut-out dimensions: 32½"w x 20"d x 12"h *
- Stainless Steel Construction including SS Sink and Mixer Faucet, Insulated Ice Chest with removable lid, Front Beverage Caddy with Towel Rack, Bottle Opener, removable Cutting Board, and Condiment Trays.



- Cut-out dimensions: 14"w x 22%"d x 12"h
- Bar Caddy comes equipped with a towel bar, bottle opener, sliding storage drawer, two stainless steel bottle sleeves and an installation hanger.
- · Available with the optional steam warming accessory.

BEVERAGE BUTLER KEY FEATURES



Stainless Steel Mixer Faucet



Removable Bamboo Cutting Board



Removable Condiment Trays



Towel Rack & Bottle Opener

^{*}An additional cutout is required for the faucet, refer to the owner's manual for complete specifications and requirements.